

GEN 2.2 ABBREVIATIONS USED IN AIS PUBLICATIONS

Abbreviations marked yellow in HTML (printed in *italics* in PDF) are either different from or not contained in ICAO Doc 8400.

A

A	amber
A	<i>FRA arrival connecting point</i>
AA	<i>approved agency</i>
AAA	(or AAB, AAC... etc., in sequence) amended meteorological message (message type designator)
A/A	air-to-air
AAD	assigned altitude deviation
AAIM	aircraft autonomous integrity monitoring
AAL	above aerodrome level
AAR	air to air refuelling
ABI	advance boundary information
ABM	abeam
ABN	aerodrome beacon
ABT	about
ABV	above
AC	altocumulus
ACARS	aircraft communication addressing and reporting system (to be pronounced "AY-CARS")
ACAS	airborne collision avoidance system (to be pronounced "AY-CAS")
ACC	area control centre or area control
ACCID	notification of an aircraft accident
ACFT	aircraft
ACK	acknowledge
ACL	altimeter check location
ACL	<i>ATC clearances and instructions</i>
ACM	<i>ATC communications management</i>
ACN	aircraft classification number
ACP	acceptance (message type designator)
ACPT	accept or accepted
ACT	active or activated or activity
AD	aerodrome
ADA	advisory area
ADC	aerodrome chart
ADDN	addition or additional
ADF	automatic direction finding equipment
ADIZ	air defence identification zone (to be pronounced "AY-DIZ")
ADJ	adjacent
ADO	aerodrome office (specify service)
ADR	advisory route
ADS	the address (when this abbreviation is used to request a repetition, the question mark (IMI) precedes the abbreviation, e.g. IMI ADS) (to be used in AFS as a procedure signal)
ADS-B	automatic dependent surveillance - broadcast
ADS-C	automatic dependent surveillance - contract
ADSU	automatic dependent surveillance unit
ADVS	advisory service
ADZ	advise
AES	aircraft earth station
AFIL	flight plan filed in the air
AFIS	aerodrome flight information service
AFISO	<i>AFIS operator</i>
AFIZ	<i>aerodrome flight information zone</i>
AFM	yes or affirm or affirmative or that is correct
AFS	aeronautical fixed service
AFT	after... (followed by time or place)
AFTN	aeronautical fixed telecommunication network
A/G	air-to-ground
AGA	aerodromes, air routes and ground aids
AGL	above ground level
AGN	again
AIC	aeronautical information circular
AIDC	air traffic services interfacility data communication
AIM	aeronautical information management
AIP	aeronautical information publication
AIRAC	aeronautical information regulation and control
AIREP	air report
AIRMET	information concerning en-route weather phenomena which may affect the safety of low-level aircraft operations
AIS	aeronautical information services
ALA	lighting area
ALERFA	alert phase
ALR	alerting (message type designator)
ALRS	alerting service
ALS	approach lighting system
ALT	altitude
ALTN	alternate or alternating (light alternates in colour)
ALTN	alternate aerodrome
AMA	area minimum altitude
AMC	<i>airspace management cell</i>
AMC	<i>ATC microphone check</i>
AMD	amend or amended (used to indicate amended meteorological message; message type designator)
AMDT	amendment (AIP amendment)

AMHS	<i>ATS message handling system</i>
AMS	aeronautical mobile service
AMSL	above mean sea level
AMSS	aeronautical mobile satellite service
ANC	aeronautical chart - 1:500 000 (followed by name/title)
ANCS	aeronautical navigation chart - small scale (followed by name/title and scale)
ANM	<i>ATFM notification message</i>
ANS	answer
AO	aircraft operator
AOC	aerodrome obstacle chart (followed by type and name/title)
AOCS	<i>air operations control station</i>
AOM	<i>airside operations manager</i>
AP	airport
APAPI	abbreviated precision approach path indicator (to be pronounced "AY-PAPI")
APCH	approach
APDC	aircraft parking/docking chart (followed by name/title)
APN	apron
APP	approach control office or approach control or approach control service
APR	April
APRX	approximate or approximately
APSG	after passing
APU	auxiliary power unit
APV	approach procedure with vertical guidance
ARC	area chart
ARINC	<i>navigation system database specification (Aeronautical Radio Incorporated)</i>
ARNG	arrange
ARO	air traffic services reporting office
ARP	aerodrome reference point
ARP	air-report (message type designator)
ARQ	automatic error correction
ARR	arrival (message type designator)
ARR	arrive or arrival
ARS	special air-report (message type designator)
ARST	arresting (specify (part of) aircraft arresting equipment)
AS	altostratus
ASAP	as soon as possible
ASC	ascent to or ascending to
ASDA	accelerate stop distance available
ASE	altimetry system error
ASHTAM	special series NOTAM notifying, by means of a specific format, change in activity of a volcano, a volcanic eruption and/or volcanic ash cloud that is of significance to aircraft operations
ASM	<i>airspace management</i>
ASPH	asphalt
ASR	<i>altimeter setting region</i>
AT	at (followed by time at which weather change is forecast to occur)
ATA	actual time of arrival
ATAS	<i>automatic telephone answering system</i>
ATC	air traffic control (in general)
ATCSMAC	air traffic control surveillance minimum altitude chart (followed by name/title)
ATD	actual time of departure
ATFM	air traffic flow management
ATIS	automatic terminal information service (to be pronounced "AY-TIS")
ATM	air traffic management
ATN	aeronautical telecommunication network
ATP	at... (followed by time or place)
ATS	air traffic services
ATTN	attention
AT-VASIS	abbreviated T visual approach slope indicator system (to be pronounced "AY-TEE-VASIS")
ATZ	aerodrome traffic zone
AUG	August
AUP	<i>airspace use plan</i>
AUTH	authorized or authorization
AUTO	automatic
AUW	all up weight
AUX	auxiliary
AVBL	available or availability
AVG	average
AVGAS	aviation gasoline
AWOS	automated weather observation system
AWTA	advise at what time able
AWY	airway
AZM	azimuth

B

B	blue
BA	braking action
BARO-VNAV	barometric vertical navigation (to be pronounced "BAA-RO-VEENAV")
BASE	cloud base

BCFG	fog patches
BCN	beacon (aeronautical ground light)
BCST	broadcast
BDRY	boundary
BECMG	becoming
BFR	before
BKN	broken
BL	blowing (followed by DU=dust, SA=sand or SN=snow)
BLDG	building
BLO	below clouds
BLW	below...
BOMB	bombing
BR	mist
BRF	short (used to indicate the type of approach desired or required)
BRG	bearing
BRKG	braking
BS	commercial broadcasting station
BTL	between layers
BTN	between
BUFR	binary universal form for the representation of meteorological data

C

C	centre (preceded by runway designation number to identify a parallel runway)
C	degrees Celsius (centigrade)
CA	course to an altitude
CAA	civil aviation authority or civil aviation administration
CADF	<i>centralized airspace data function</i>
CAT	category
CAT	clear air turbulence
CAVOK	visibility, cloud and present weather better than prescribed values or conditions (to be pronounced "KAV-OH-KAY")
CB	cumulonimbus (to be pronounced "CEE BEE")
CBA	<i>cross border area</i>
CC	cirrocumulus
CCA	(or CCB, CCC...etc., in sequence) corrected meteorological message (message type designator)
CCO	continuous climb operations
CD	candela
CDA	<i>continuous descent approach</i>
CDM	<i>collaborative decision making</i>
CDN	co-ordination (message type designator)
CDO	continuous descent operations
CDR	<i>conditional route</i>
CF	change frequency to...
CF	course to a fix
CFM	confirm or I confirm (to be used in AFS as a procedure signal)
CGL	circling guidance light(s)
CH	channel
CH	this is a channel-continuity-check of transmission to permit comparison of your record of channel-sequence numbers of messages received on the channel (to be used in AFS as a procedure signal)
CHEM	chemical
CHG	modification (message type designator)
CI	cirrus
CIDIN	common ICAO data interchange network
CIV	civil
CK	check
CL	centre line
CLA	clear type of ice formation
CLBR	calibration
CLD	cloud
CLG	calling
CLIMB-OUT	climb-out area
CLR	clear(s) or cleared to... or clearance
CLRD	runway(s) cleared (used in METAR/SPECI)
CLSD	close or closed or closing
CM	centimetre
CMB	climb to or climbing to
CMPL	completion or completed or complete
CNL	cancel or cancelled
CNL	flight plan cancellation (message type designator)
CNS	communications, navigation and surveillance
COM	communications
CONC	concrete
COND	condition
CONS	continuous
CONST	construction or constructed
CONT	continue(s) or continued
COOR	co-ordinate or co-ordination
COORD	co-ordinates
COP	change-over point
COR	correct or correction or corrected (used to indicate corrected meteorological message; message type designator)
COT	at the coast
COV	cover or covered or covering
CPDLC	controller-pilot data link communications
CPL	current flight plan (message type designator)
CRC	cyclic redundancy check

CRM	collision risk model
CRP	compulsory reporting point
CRZ	cruise
CS	call sign
CS	cirrostratus
CTA	control area
CTAM	climb to and maintain
CTC	contact
CTL	control
CTN	caution
CTOT	<i>calculated take-off time</i>
CTR	control zone
CU	cumulus
CUF	cumuliform
CUST	customs
CVR	cockpit voice recorder
CW	continuous wave
CWY	clearway

D

D	danger area (followed by identification)
D	downward (tendency in RVR during previous 10 minutes)
D	<i>FRA departure connecting point</i>
DA	decision altitude
D-ATIS	data link automatic terminal information service (to be pronounced "DEE-ATIS")
DCD	double channel duplex
DCKG	docking
DCP	datum crossing point
DCPC	direct controller-pilot communications
DCS	double channel simplex
DCT	direct (in relation to flight plan clearances and type of approach)
DE	from (used to precede the call sign of the calling station) (to be used in AFS as a procedure signal)
DEC	December
DEG	degrees
DEP	depart or departure
DEP	departure (message type designator)
DEPO	deposition
DER	departure end of the runway
DES	descend to or descending to
DEST	destination
DETRESFA	distress phase
DEV	deviation or deviating
DF	direction finding
DFDR	digital flight data recorder
DFTI	distance from touchdown indicator
DH	decision height
DIF	diffuse
DIST	distance
DIV	divert or diverting
DLA	delay or delayed
DLA	delay (message type designator)
DLIC	data link initiation capability
DLY	daily
DME	distance measuring equipment
DNG	danger or dangerous
DOF	date of flight
DOM	domestic
DP	dew point temperature
DPT	depth
DR	dead reckoning
DR	low drifting (followed by DU=dust, SA=sand or SN=snow)
DRG	during
DS	duststorm
DSB	double sideband
DTAM	descend to and maintain
DTG	date-time group
DTHR	displaced runway threshold
DTRT	deteriorate or deteriorating
DTW	dual tandem wheels
DU	dust
DUC	dense upper cloud
DUPE	this is a duplicate message (to be used in AFS as a procedure signal)
DUR	duration
D-VOLMET	data link VOLMET
DVOR	Doppler VOR
DVORTAC	<i>Doppler VOR and TACAN</i>
DW	dual wheels
DZ	drizzle

E

E	east or eastern longitude
E	<i>FRA horizontal entry point</i>
EASA	<i>European Aviation Safety Agency</i>
EAT	expected approach time
EAUP	<i>European airspace use plan</i>
EB	eastbound
ECAC	<i>European civil aviation conference</i>
EDA	elevation differential area
EDTO	extended diversion time operation

EEE	error (to be used in AFS as a procedure signal)	FPR	flight plan route
EET	estimated elapsed time	FR	fuel remaining
EFC	expect further clearance	FRA	<i>free route airspace</i>
EFCT	<i>expected further clearance time</i>	FREQ	frequency
EFIS	electronic flight instrument system (to be pronounced "EE-FIS")	FRI	Friday
eFPL	filed flight plan exchanged via flight and flow - information for a collaborative environment (FF-ICE) services	FRNG	firing
EGNOS	European geostationary navigation overlay service (to be pronounced "EGG-NOS")	FRONT	front (relating to weather)
EHF	extremely high frequency (30 000 to 300 000 MHz)	FROST	frost (used in aerodrome warnings)
ELBA	emergency location beacon - aircraft	FRQ	frequent
ELEV	elevation	FSC	<i>flight service centre</i>
ELR	extra long range	FSL	full stop landing
ELT	emergency locator transmitter	FSS	flight service station
EM	emission	FST	first
EMBD	embedded in a layer (to indicate cumulonimbus embedded in layers of other clouds)	ft	feet (dimensional unit)
EMERG	emergency	FT	feet (dimensional unit)
En	<i>English</i>	FTE	flight technical error
END	stop-end (related to RVR)	FTP	fictitious threshold point
ENE	east-north-east	FTT	flight technical tolerance
ENG	engine	FU	smoke
ENR	en-route	FUA	<i>flexible use of airspace</i>
ENRC	en-route chart (followed by name/title)	FZ	freezing
EOBT	estimated off-block time	FZDZ	freezing drizzle
EQPT	equipment	FZFG	freezing fog
ESE	east-south-east	FZRA	freezing rain
EST	estimate or estimated or estimate (as message type designator)		
ETA	estimated time of arrival or estimating arrival	G	
ETD	estimated time of departure or estimating departure	G	green
ETO	estimated time over significant point	G	variations from the mean wind speed (gusts) (followed by figures in METAR/SPECI and TAF)
EUR RODEX	European regional OPMET data exchange	GA	general aviation
EUUP	<i>European updated airspace use plan</i>	GA	go ahead, resume sending (to be used in AFS as a procedure signal)
EV	every	G/A	ground-to-air
EVS	enhanced vision system	G/A/G	ground-to-air and air-to-ground
EXC	except	GAGAN	GPS and geostationary earth orbit augmented navigation
EXER	exercises or exercising or to exercise	GAIN	airspeed or headwind gain
EXP	expect or expected or expecting	GAMET	area forecast for low-level flights
EXTD	extend or extending or extended	GARP	GBAS azimuth reference point
		GAT	<i>general air traffic</i>
		GBAS	ground-based augmentation system (to be pronounced "GEE-BAS")
F		GCA	ground controlled approach system or ground controlled approach
F	fixed	GEN	general
FA	course from a fix to an altitude	GEO	geographic or true
FAC	facilities	GES	ground earth station
FAF	final approach fix	GHz	<i>giga Hertz (= 1000 MHz)</i>
FAL	facilitation of international air transport	GLD	glider
FANS	<i>future air navigation system</i>	GLLFC	<i>graphical low-level forecast</i>
FAP	final approach point	GLONASS	global orbiting navigation satellite system (to be pronounced "GLO-NAS")
FAS	final approach segment	GLS	GBAS landing system
FATO	final approach and take-off area	GLV	<i>groep lichte vliegtuigen</i>
FAVA	<i>final approach vectoring area</i>	GMC	ground movement chart (followed by name/title)
FAX	facsimile transmission	GND	ground
FBL	light (used to indicate the intensity of weather phenomena, interference or static reports, e.g. FBL RA=light rain)	GNDCK	ground check
FBZ	<i>flight planning buffer zone</i>	GNSS	global navigation satellite system
FC	tunnel cloud (tornado or water spout)	GOV	government
FCST	forecast	GP	glide path
FCT	friction coefficient	GPA	glide path angle
FDPS	flight data processing system	GPIP	glide path intercept point
FEB	February	GPS	global positioning system
FEW	few	GPU	ground power unit
FG	fog	GPWS	ground proximity warning system
FIC	flight information centre	GR	hail
FIO	<i>flight information office</i>	GRAS	ground-based regional augmentation system (to be pronounced "GRASS")
FIR	flight information region	GRASS	grass landing area
FIS	flight information service	GRIB	processed meteorological data in the form of grid point values expressed in binary form (meteorological code)
FISA	automated flight information service	GRVL	gravel
FI	<i>flashing</i>	GS	ground speed
FL	flight level	GS	small hail and/or snow pellets
FLD	field	GUND	geoid undulation
FLG	flashing		
FLR	flares	H	
FLT	flight	H	high pressure area or the centre of high pressure
FLTCK	flight check	H	significant wave height (followed by figures in METAR/SPECI)
FLUC	fluctuating or fluctuation or fluctuated	H	<i>hourly</i>
FLW	follow(s) or following	h	<i>half-hourly</i>
FLY	fly or flying	H24	continuous day and night service
FM	course from a fix to manual termination (used in navigation database coding)	HA	holding/racetack to an altitude
FM	from	HAP	<i>heli aiming point</i>
FM	from (followed by time weather change is forecast to begin)	HAPI	helicopter approach path indicator
FMC	flight management computer	HBN	hazard beacon
FMC	<i>frequency monitoring code</i>	HCH	helicopter crossing height
FMP	<i>flow management position</i>	HDF	high frequency direction finding station
FMS	flight management system	HDG	heading
FMU	flow management unit	HEL	helicopter
FNA	final approach	HEMS	<i>helicopter emergency medical service</i>
FPAP	flight path alignment point	HF	high frequency (3000 to 30 000 kHz)
FPL	filed flight plan exchanged via aeronautical fixed service (AFS)	HF	holding/racetack to a fix
FPM	feet per minute		

© Air Traffic Control the Netherlands

MET	local routine meteorological report (in abbreviated plain language)	NNW	north-north-west
REPORT		NO	no (negative) (to be used in AFS as a procedure signal)
MF	medium frequency (300 to 3000 kHz)	NOF	international NOTAM office
MFA	<i>minimum flight altitude</i>	NONSTD	non-standard
MHA	minimum holding altitude	NOSIG	no significant change (used in trend-type landing forecasts)
MHDF	medium and high frequency direction finding stations (at the same location)	NOTAM	a notice distributed by means of telecommunication containing information concerning the establishment, condition or change in any aeronautical facility, service, procedure or hazard, the timely knowledge of which is essential to personnel concerned with flight operations
MHVDF	medium, high and very high frequency direction finding stations (at the same location)		
MHz	megahertz	NOTAMC	cancelling NOTAMN
MID	mid-point (related to RVR)	NOTAMN	new NOTAM
MIFG	shallow fog	NOTAMR	replacing NOTAM
MIL	military	NOV	November
MILATCC	<i>military air traffic control centre</i>	NOZ	normal operating zone
MIN	minutes	NPA	non-precision approach
MIS	missing... (transmission identification) (to be used in AFS as a procedure signal)	NR	number
MKR	marker radio beacon	NRH	no reply heard
MLA	<i>microlight aeroplane</i>	NS	nimbostratus
MLH	<i>microlight helicopter</i>	NSC	nil significant cloud
MLS	microwave landing system	NSE	navigation system error
MLW	<i>maximum certificated landing weight</i>	NSW	nil significant weather
MM	middle marker	NTL	national
MNM	minimum	NTZ	no transgression zone
MNPS	minimum navigation performance specifications	NU	<i>not usable</i>
MNT	monitor or monitoring or monitored	NW	north-west
MNTN	maintain	NW	<i>nieuw in "Nw Milligen"</i>
MOA	military operating area	NWB	<i>north-westbound</i>
MOC	minimum obstacle clearance (required)	NXT	next
MOCA	minimum obstacle clearance altitude		
MOD	moderate (used to indicate the intensity of weather phenomena, interference of static reports, e.g. MODRA=moderate rain)	O	
MOGAS	<i>motor gasoline (premiumgrade or fourstar)</i>	OAC	oceanic area control centre
MON	above mountains	OAS	obstacle assessment surface
MON	Monday	OAT	<i>operational air traffic (military)</i>
MOPS	minimum operational performance standards	OBS	observe or observed or observation
MOV	move or moving or movement	OBSC	obscure or obscured or obscuring
MPa	<i>megapascal</i>	OBST	obstacle
MPS	metres per second	OCA	obstacle clearance altitude
MRA	minimum reception altitude	OCA	oceanic control area
MRG	medium range	OCC	occluding (light)
MRP	ATS/MET reporting point	OCH	obstacle clearance height
MRVA	<i>minimum radar vector altitude</i>	OCNL	occasional or occasionally
MS	minus	OCS	obstacle clearance surface
MSA	minimum sector altitude	OCT	October
MSAS	multi-functional transport satellite (MTSAT) satellite-based augmentation system (to be pronounced "EM-SAS")	OFZ	obstacle free zone
MSAW	minimum safe altitude warning	OGN	originate (to be used in AFS as a procedure signal)
MSG	message	OHD	overhead
MSL	mean sea level	OIS	obstacle identification surface
MSR	message... (transmission identification) has been misrouted (to be used in AFS as a procedure signal)	OK	we agree or it is correct (to be used in AFS as a procedure signal)
MSSR	monopulse secondary surveillance radar	OLDI	online data interchange
MT	mountain	OM	outer marker
MTI	<i>marked temperature inversion</i>	OPA	opaque, white type of ice formation
MTOM	maximum take-off mass	OPC	control indicated is operational control
MTU	metric units	OPMET	operational meteorological (information)
MTW	mountain waves	OPN	open or opening or opened
MUAC	<i>Maastricht Upper Area Control centre</i>	OPR	operator or operate or operative or operating or operational
MVA	<i>minimum vectoring altitudes</i>	OPS	operations
MVDF	medium and very high frequency direction finding stations (at the same location)	O/R	on request
MWO	meteorological watch office	ORD	order
MX	mixed type of ice formation (white and clear)	OSV	ocean station vessel
		OTP	on top
		OTS	organized track system
		OUBD	outbound
		OVC	overcast
N		P	
N	no distinct tendency (in RVR during previous 10 minutes)	P	maximum value of wind speed or runway visual range (followed by figures in METAR/SPECI and TAF)
N	north or northern latitude	P	prohibited area (followed by identification)
NA	<i>not applicable</i>	PA	precision approach
NADP	noise abatement departure procedure	PALS	precision approach lighting system (specify category)
NAF	<i>North Sea Area Forecast</i>	PANS	procedures for air navigation services
NASC	national AIS system centre	PAPI	precision approach path indicator
NAT	North Atlantic	PAR	precision approach radar
NAV	navigation	PARL	parallel
NAVAID	navigation aid	PATC	precision approach terrain chart (followed by name/title)
NB	northbound	PAX	passenger(s)
NBFR	not before	PBC	performance-based communication
NC	no change	PBN	performance-based navigation
NCD	no cloud detected (used in automated METAR/SPECI)	PBS	performance-based surveillance
NDB	non-directional radio beacon	PCD	proceed or proceeding
NDV	no directional variations available (used in automated METAR/SPECI)	PCL	pilot-controlled lighting
NE	north-east	PCN	pavement classification number
NEB	north-eastbound	PCR	pavement classification rating
NEG	no or negative or permission not granted or that is not correct	PCT	per cent
NGT	night	PDC	pre-departure clearance
NIL	none or I have nothing to send to you	PDG	procedure design gradient
NM	nautical miles	PDT	<i>procedure design tool</i>
NML	normal	PER	performance
NMOC	<i>Network Manager Operation Center</i>	PERM	permanent
NN	no name, unnamed	PFC	<i>porous friction course</i>
NNE	north-north-east	PFP	preliminary flight plan

PIB	pre-flight information bulletin	RCLL	runway centre line light(s)
PJE	parachute jumping exercise	RCLR	recleared
PL	<i>plain language</i>	RCP	required communication performance
PL	ice pellets	RCR	<i>runway condition report</i>
PLA	practice low approach	RDH	reference datum height
PLVL	present level	RDL	radial
PN	prior notice required	RDO	radio
PNR	point of no return	RDOACT	radioactive
PO	dust/sand whirls (dust devils)	RE	recent (used to qualify weather phenomena e.g. RERA=recent rain)
POB	persons on board	REC	receive or receiver
POSS	possible	RECAT-EU	<i>European wake vortex re-categorization</i>
PPI	plan position indicator	REDL	runway edge light(s)
PPR	prior permission required	REF	reference to... or refer to ...
PPSN	present position	REG	registration
PRFG	aerodrome partially covered by fog	RENL	runway end light(s)
PRI	primary	REP	report or reporting or reporting point
PRKG	parking	REQ	request or requested
PROB	probability	ERTE	re-route
PROC	procedure	RESA	runway end safety area
PROP	propeller	RETD	<i>revised estimated time of departure</i>
PROV	provisional	RF	constant radius arc to a fix
PRP	point-in-space reference point	RFFS	rescue and fire fighting services
PS	plus	RFP	<i>replacement flight plan</i>
PSI	<i>pounds per square inch</i>	RG	range (lights)
PSG	passing	RHC	right-hand circuit
PSN	position	RIF	reclearance in flight
PSP	pierced steel plank	RIME	rim (used in aerodrome warnings)
PSR	primary surveillance radar	RL	report leaving
PSYS	pressure system(s)	RLA	relay to
PTN	procedure turn	RLCE	request level change en-route
PTS	polar track structure	RLLS	runway lead-in lighting system
PWR	power	RLNA	request level not available
Q		RMK	remark
QDL	do you intend to ask me for a series of bearings? or I intend to ask you for a series of bearings (to be used in radiotelegraphy as a Q code)	RMZ	<i>radio mandatory zone</i>
QDM	magnetic heading (zero wind)	RNAV	area navigation (to be pronounced "AR-NAV")
QDR	magnetic bearing	RNG	radio range
QFE	atmospheric pressure at aerodrome elevation (or at runway threshold)	RNLAF	<i>Royal Netherlands Airforce</i>
QFU	magnetic orientation of runway	RNN	<i>Royal Netherlands Navy</i>
QGE	what is my distance to your station? or your distance to my station is (distance figures and units) (to be used in radiotelegraphy as a Q code)	RNP	required navigation performance
QJH	shall I run my test tape/a test sentence? or run your test tape/a test sentence (to be used in AFS as a Q code)	ROBEX	regional OPMET bulletin exchange (scheme)
QNH	altimeter sub-scale setting to obtain elevation when on the ground	ROC	rate of climb
QSP	will you relay to... free of charge? or I will relay to... free of charge (to be used in AFS as a Q code)	ROD	rate of descent
QTA	shall I cancel telegram number...? or cancel telegram number... (to be used in AFS as a Q code)	RON	receiving only
QTE	true bearing	RPAS	<i>remotely piloted aircraft systems</i>
QTF	will you give me the position of my station according to the bearings taken by the D/F stations which you control? or the position of your station according to the bearings taken by the D/F stations that I control was... latitude... longitude (or other indication of position), class... at... hours (to be used in radiotelegraphy as a Q code)	RPDS	reference path data selector
QUAD	quadrant	RPI	radar position indicator
QUJ	will you indicate the TRUE track to reach you? or the TRUE track to reach me is... degrees at... hours (to be used in radiotelegraphy as a Q code)	RPL	repetitive flight plan
R		RPLC	replace or replaced
R	radial from VOR (followed by three figures)	RPS	radar position symbol
R	rate of turn	RPT	repeat or I repeat (to be used in AFS as a procedure signal)
R	received (acknowledgement of receipt) (to be used in AFS as a procedure signal)	RQ	request (to be used in AFS as a procedure signal)
R	red	RQMNTS	requirements
R	restricted area (followed by identification)	RQP	request flight plan (message type designator)
R	right (preceded by runway designation number to identify a parallel runway)	RQS	request supplementary flight plan (message type designator)
R	runway (followed by figures in METAR/SPECI)	RR	report reaching
RA	rain	RRA	(or RRB, RRC...etc., in sequence) delayed meteorological message (message type designator)
RA	resolution advisory	RSA	<i>restricted airspace</i>
RAC	rules of the air and air traffic services	RSC	rescue sub-centre
RAD	<i>route availability document</i>	RSCD	runway surface condition
RAG	ragged	RSM	<i>runway state message</i>
RAG	runway arresting gear	RSP	required surveillance performance
RAI	runway alignment indicator	RSP	responder beacon
RAIM	receiver autonomous integrity monitoring	RSR	en-route surveillance radar
RAPCON	<i>radar approach control</i>	RSS	root sum square
RASC	regional AIS system centre	RTD	delayed (used to indicate delayed meteorological message; message type designator)
RASS	remote altimeter setting source	RTE	route
RB	rescue boat	RTF	radiotelephone
RCA	reach cruising altitude	RTG	radiotelegraph
RCAM	<i>runway condition assessment matrix</i>	RTHL	runway threshold light(s)
RCC	rescue co-ordination centre	RTN	return or returned or returning
RCF	radio communication failure (message type designator)	RTODAH	rejected take-off distance available, helicopter
RCH	reach or reaching	RTS	return to service
RCL	runway centre line	RTT	radioteletypewriter
		RTZL	runway touchdown zone light(s)
		RUT	standard regional route transmitting frequencies
		RV	rescue vessel
		RVA	radar vectoring area
		RVR	runway visual range
		RVSM	reduced vertical separation minimum (300 m (1000 ft)) between FL 290 and FL 410
		RWY	runway
		RWYCC	<i>runway condition code</i>
S		S	south or southern latitude
		S	<i>special meteorological report (in abbreviated plain language)</i>
		S	state of the sea (followed by figures in METAR/SPECI)
		SA	sand
		SALS	simple approach lighting system
		SAN	sanitary

SAR	search and rescue	SUP	supplement (AIP supplement)
SARPS	standards and recommended practices (ICAO)	SUPPS	regional supplementary procedures
SAT	Saturday	SVC	service (message type only)
SATCOM	satellite communication (used only when referring generally to both voice and data satellite communication or only data satellite communication)	SVCBL	serviceable
SATVOICE	satellite voice communication	SW	south-west
SB	southbound	SWB	south-westbound
SBAS	satellite-based augmentation system (to be pronounced "ESS-BASS")	SWC	<i>significant weather chart</i>
SC	stratocumulus	SWY	stopway
SCT	scattered	T	
SD	standard deviation	T	temperature
SDBY	stand by	T	true (preceded by a bearing to indicate reference to true north)
SDF	step down fix	TA	traffic advisory
SE	south-east	TA	transition altitude
SEA	sea (used in connection with sea-surface temperature and state of the sea)	TAA	terminal arrival altitude
SEB	south-eastbound	TACAN	UHF tactical air navigation aid
SEC	seconds	TAF	aerodrome forecast (in meteorological code)
SECN	section	TA/H	turn at an altitude/height
SECT	sector	TAIL	tail wind
SELCAL	selective calling system	TAR	terminal area surveillance radar
SEP	September	TAS	true airspeed
SER	service or servicing or served	TAX	taxiing or taxi
SERA	<i>standardised European rules of the air</i>	TBS	<i>Time based separation</i>
SEV	severe (used e.g. to qualify icing and turbulence reports)	TC	tropical cyclone
SFC	surface	TCAC	tropical cyclone advisory centre
SG	snow grains	TCAS RA	traffic alert and collision avoidance system resolution advisory (to be pronounced "TEE-CAS-AR-AY")
SGL	signal	TCH	threshold crossing height
SH	showers (followed by RA=rain, SN=snow, PL=ice pellets, GR=hail, GS=small hail and/or snow pellets or combinations thereof, e.g. SHRASN=showers of rain and snow)	TCU	towering cumulus
SHF	super high frequency (3000 to 30 000 MHz)	TDO	tornado
SI	international system of units	TDZ	touchdown zone
SID	standard instrument departure	TECR	technical reason
SIF	selective identification feature	TEL	telephone
SIG	significant	TEMPO	temporary or temporarily
SIGMET	information concerning en-route weather and other phenomena in the atmosphere that may affect the safety of aircraft operations	TF	track to fix
SIMUL	simultaneous or simultaneously	TFC	traffic
SIWL	single isolated wheel load	TGL	touch-and-go landing
SKED	schedule or scheduled	TGL	<i>temporary guidance leaflet</i>
SLP	speed limiting point	TGS	taxiing guidance system
SLW	slow	THR	threshold
SMC	surface movement control	THRU	through
SMR	surface movement radar	THU	Thursday
SN	snow	TIBA	traffic information broadcast by aircraft
SNOCLO	aerodrome closed due to snow (used in METAR/SPECI)	TIL	until
SNOWTAM	special series NOTAM notifying the presence or removal of hazardous conditions due to snow, ice, slush or standing water associated with snow, slush and ice on the movement area, by means of a specific format	TIP	until past... (place)
SOC	start of climb	TKOF	take-off
SPECI	aerodrome special meteorological report (in meteorological code)	TL	till (followed by time by which weather change is forecast to end)
SPECIAL	special local meteorological report (in abbreviated plain language)	TLOF	touchdown and lift-off area
SPI	special position indicator	TMA	terminal control area
SPL	supplementary flight plan (message type designator)	TMG	<i>touring motor glider</i>
SPOC	SAR point of contact	TMZ	<i>transponder mandatory zone</i>
SPOT	spot wind	TN	minimum temperature (followed by figures in TAF)
SQ	squall	TNA	turn altitude
SQL	squall line	TNH	turn height
SR	sunrise	TO	to... (place)
SR-30	<i>30 minutes before sunrise</i>	TOBT	<i>target off-block time</i>
SRA	surveillance radar approach	TOC	top of climb
SRE	surveillance radar element of precision approach radar system	TODA	take-off distance available
SRG	short range	TODAH	take-off distance available, helicopter
SRR	search and rescue region	TOP	cloud top
SRY	secondary	TORA	take-off run available
SS	sandstorm	TOX	toxic
SS	sunset	TP	turning point
SS+30	<i>30 minutes after sunset</i>	TR	track
SSB	single sideband	TRA	temporary reserved airspace
SSE	south-south-east	TRANS	transmits or transmitter
SSR	secondary surveillance radar	TREND	trend forecast
SST	supersonic transport	TRG	training
SSW	south-south-west	TRL	transition level
ST	stratus	TROP	tropopause
STA	straight-in approach	TS	thunderstorm (in aerodrome reports and forecasts, TS used alone means thunder heard but no precipitation at the aerodrome)
STAR	standard instrument arrival	TS	thunderstorm (followed by RA=rain, SN=snow, PL=ice pellets, GR=hail GS=small hail and/or snow pellets or combinations thereof, e.g. TSRASN=thunderstorm with rain and snow)
STD	standard	TSA	<i>temporary segregated area</i>
STF	stratiform	TSAT	<i>target start-up approval time</i>
STN	station	TSUNAMI	tsunami (used in aerodrome warnings)
STNR	stationary	TT	teletypewriter
STOL	short take-off and landing	TUE	Tuesday
STS	status	TURB	turbulence
STWL	stopway light(s)	T-VASIS	T visual approach slope indicator system (to be pronounced "TEE-VASIS")
SUBJ	subject to	TVOR	terminal VOR
SUN	Sunday	TWR	aerodrome control tower or aerodrome control
		TWY	taxiway
		TX	maximum temperature (followed by figures in TAF)
		TXL	taxilane

TXT	text (when the abbreviation is used to request a repetition, the question mark (IMI) precedes the abbreviation, e.g. IMI TXT) (to be used in AFS as a procedure signal)	WAFC	world area forecast centre
TYP	type of aircraft	WB	westbound
TYPH	typhoon	WBAR	wing bar lights
U		WDI	wind direction indicator
U	upward (tendency in RVR during previous 10 minutes)	WDSPR	widespread
UA	unmanned aircraft	WED	Wednesday
UAB	until advised by ...	WEF	with effect from or effective from
UAC	upper area control centre	WGS-84	world geodetic system - 1984
UAR	upper air route	WI	within
UAS	unmanned aircraft system	WID	width or wide
UDA	<i>upper advisory area</i>	WIE	with immediate effect or effective immediately
UDF	ultra high frequency direction finding station	WILCO	will comply
UDP	<i>uniform daylight period</i>	WIND	wind
UDR	<i>upper advisory route</i>	WIP	work in progress
UFN	until further notice	WKN	weaken or weakening
UHDT	unable higher due traffic	WNW	west-north-west
UHF	ultra high frequency (300 to 3000 MHz)	WO	without
UIC	upper information centre	WPT	waypoint
UIR	upper flight information region	WRNG	warning
ULM	ultra light motorized aircraft	WS	wind shear
ULR	ultra long range	WSPD	wind speed
UNA	unable	WSW	west-south-west
UNAP	unable to approve	WT	weight
UNL	unlimited	WTC	<i>wake turbulence category</i>
UNREL	unreliable	WTSPT	waterspout
UP	unidentified precipitation (used in METAR/SPECI)	WWW	world wide web
URL	<i>uniform resource locator</i>	WX	weather
U/S	unserviceable	WXR	weather radar
UTA	upper control area	X	
UTC	co-ordinated universal time	X	cross
UUP	<i>updated airspace use plan</i>	X	<i>FRA horizontal exit point</i>
V		XBAR	crossbar (of approach lighting system)
V	variations from the mean wind direction (preceded and followed by figures in METAR/SPECI, e.g. 350V070)	XNG	crossing
VA	heading to an altitude	XS	atmospherics
VA	volcanic ash	Y	
VAAC	volcanic ash advisory centre	Y	yellow
VAC	visual approach chart (followed by name/title)	YCYZ	yellow caution zone (runway lighting)
VAL	in valleys	YES	yes (affirmative) (to be used in AFS as a procedure signal)
VAN	runway control van	YR	your
VAR	magnetic variation	Z	
VAR	visual-aural radio range	Z	co-ordinated universal time (in meteorological messages)
VASIS	visual approach slope indicator systems		
VB	<i>during day when visibility is bad</i>		
VC	vicinity of the aerodrome (followed by FG=fog, FC=funnel cloud, SH=showers, PO=dust/sand whirls, BLDU=blowing dust, BLSA=blowing sand, BLSN=blowing snow, DS=dust-storm, SS=sandstorm, TS=thunderstorm or VA=volcanic ash, e.g. VCFG=vicinity fog)		
VCY	vicinity		
VDF	very high frequency direction finding station		
VDGS	<i>visual docking guidance system</i>		
VER	vertical		
VFR	visual flight rules		
VHF	very high frequency (30 to 300 MHz)		
VI	heading to an intercept		
VIP	very important person		
VIS	visibility		
VLF	very low frequency (3 to 30 kHz)		
VLR	very long range		
VM	heading to a manual termination		
VMC	visual meteorological conditions		
VN	<i>chart of visibility and cloud layers</i>		
VNAV	vertical navigation (to be pronounced "VEE-NAV")		
VOL	volume (followed by I, II...)		
VOLMET	meteorological information for aircraft in flight		
VOR	VHF omnidirectional radio range		
VORTAC	VOR and TACAN combination		
VOT	VOR airborne equipment test facility		
VPA	vertical path angle		
VPT	visual manoeuvre with prescribed track		
VRB	variable		
VSA	by visual reference to the ground		
VSP	vertical speed		
VTF	vector to final		
VTOL	vertical take-off and landing		
VV	vertical visibility (followed by figures in METAR/SPECI and TAF)		
VWS	<i>vertical wind shear</i>		
W			
W	west or western longitude		
W	white		
W	sea-surface temperature (followed by figures in METAR/SPECI)		
W	<i>upper wind chart</i>		
WAAS	wide area augmentation system		
WAC	world aeronautical chart ICAO 1:1 000 000 (followed by name/title)		