© LVNL

AD ELEV -12

TWR 135.180 Lelystad Tower
123.830
123.680 Lelystad Delivery
ATIS 120.730 Lelystad Information

VAR 2° E (2020)

ANNUAL RATE
OF CHANGE 9' E

Helicopter training:

1. Helicopter exercise area (HELEX) AVBL northeast of FATO for helicopter exercises up to 50 FT.
2. FATO and HELEX only AVBL for local helicopter training operators.
3. FATO and HELEX only AVBL during UDP.

HOTSPOT
CAUTION:
DO NOT CROSS
THE HOLDING POSITION
MARKING WITHOUT
A CLEARANCE

TRAFFIC 6 FT

PRECISION APPROACH
LIGHTING SYSTEM (CAT I)

LOC
ILSN 108.550

TERMINAL

L-apron

CWY
60 x 150 M

DTHR 300 M
ELEV -12 FT
GUND 141 FT

DISPLACED
RWY END 05
300 M

Museum
Aviodrome

Anemo-
meter

PAPI

HELICOPTER
EXERCISE AREA

Fuel station Charlie

ACL: APRON -12:6

AIS/MET
TERMINAL

TWR
72

D-Apron

Fuel station Delta

FATO

TLOF

STRIP 2700 x 280 M
RWY 05/23 2700 x 45 M

ARP
522712N
0053050E

H-Apron

Inset

PRECISION APPROACH
LIGHTING SYSTEM (CAT I)

PAPI

Anemo-
meter

GP
329.750

Meteo

DISPLACED
RWY END 23
300 M

DTHR 300 M
ELEV -13 FT
GUND 141 FT

CWY
60 x 150 M

See Inset

LELYSTAD/ILSN
CH22Y
522652N 0053027E
0

HOTSPOT
CAUTION:
DO NOT CROSS
THE HOLDING POSITION
MARKING WITHOUT
A CLEARANCE

DIRECTIONS ARE MAGNETIC
ELEVATIONS IN FEET AMSL
DIMENSIONS IN METRES

SCALE 1 : 12 500

metres 0 100 200 300 400 500
feet 0 500 1000 1500

NOTES

RWY 05:
Do not cross red lights indicating displaced RWY end.
No lights beyond displaced RWY end.
RWY 23:
Do not cross red lights indicating displaced RWY end.
No lights beyond displaced RWY end.

LEGEND

- RWY HOLDING POSITION MARKING, PATTERN A
- 6 MAX WHEEL SPAN 6M
- ATC BDRY
- BLAST FENCE
- AIR TAXI ROUTE
- RWY END LIGHTS
- RWY GUARD LIGHTS

PHYSICAL CHARACTERISTICS				
RWY	DIRECTION	BEARING STRENGTH	SURFACE	THR COORDINATES
05	046°	PCN 55/F/B/W/T	ASPH	522648N 0053010E
23	226°	PCN 55/F/B/W/T	ASPH	522734N 0053132E

CHANGE: HOTSPOTS added; editorial.