AIP NETHERLANDS ENR 1.12-1
08 JAN 2015

ENR 1.12 INTERCEPTION OF CIVIL AIRCRAFT

The interception procedures for civil aircraft will conform to Regulation (EU) No 923/2012 (SERA), ICAO Annexes 2 and 11, and Doc 4444 (PANS-ATM).

1 GENERAL

Interception of civil aircraft will normally be limited to those instances where it is essential for the safe flight of the aircraft.

All possible efforts will be made to secure identification of an aircraft, which may be a civil aircraft, by means of effective co-ordination between the appropriate military units and the civil/military air traffic services units. Consequently there is no necessity for the establishment of designated areas or routes where special procedures are required in order to avoid the possible need for interception for the purpose of identification.

If, however, identification cannot be established by these means, interception procedures may be used as a last resort in accordance with the manoeuvres recommended in Annex 2, Attachment A, paragraph 3.

During interception manoeuvres, State aircraft take due account of the performance limitations of civil aircraft, the need to avoid flying in such proximity to the intercepted aircraft that a collision hazard may be created and the need to avoid crossing the aircraft's flight path in a manner that may create hazardous wake turbulence.

If it is considered necessary to intervene in the navigation of the intercepted aircraft, the intercepting aircraft will normally take up a position on the left (port) side slightly above and ahead of the intercepted aircraft, to enable the pilot-in-command of the latter aircraft to observe the visual signals given.

The visual signals used by intercepting aircraft will be those given further in this section.

2 PROCEDURES FOR INTERCEPTED AIRCRAFT (SERA.11015)

Note: the word 'interception' in this context does not include intercept and escort service provided, on request, to an aircraft in distress, in accordance with the Search and Rescue Manual (ICAO Doc 9731).

An aircraft which is intercepted by another aircraft shall immediately:

- 1. Follow the instructions given by the intercepting aircraft, interpreting and responding to visual signals in accordance with the specifications further in this chapter.
- 2. Notify, if possible, the appropriate air traffic services unit.
- 3. Attempt to establish radio communication with the intercepting aircraft or with the appropriate intercept control unit, by making a general call on the emergency frequency 121.500 MHz, giving the identity of the aircraft and the nature of the flight; and if no contact has been established and if practicable, repeating this call on the emergency frequency 243.000 MHz.
- 4. If equipped with SSR transponder, select Mode A code 7700, unless otherwise instructed by the appropriate air traffic services unit.
- 5. If equipped with ADS-B or ADS-C, select the appropriate emergency functionality, if available, unless otherwise instructed by the appropriate air traffic services unit.

If any instructions received by radio from any sources conflict with those given by the intercepting aircraft by visual signals, the intercepted aircraft shall request immediate clarification while continuing to comply with the visual instructions given by the intercepting aircraft.

If any instructions received by radio from any sources conflict with those given by the intercepting aircraft by radio, the intercepted aircraft shall request immediate clarification while continuing to comply with the radio instructions by the intercepting aircraft.

3 RADIO COMMUNICATION DURING INTERCEPTION

If radio contact is established during interception but communication in a common language is not possible, attempts shall be made to convey instructions, acknowledgement of instructions and essential information by using the following phrases and pronunciations and transmitting each phrase twice.

3.1 By the intercepting aircraft

Phrase	Pronunciation ¹⁾	Meaning
CALL SIGN	KOL SA-IN	What is your call sign?
FOLLOW	FOL-LO	Follow me
DESCEND	DEE- SEND	Descend for landing
YOU LAND	YOU LAAND	Land at this aerodrome
PROCEED	PRO- SEED	You may proceed

3.2 By the intercepted aircraft

Phrase	Pronunciation ¹⁾	Meaning
CALL SIGN (Call sign ²⁾)	KOL SA-IN (Call sign)	My call sign is (call sign)
WILCO	VILL-KO	Understood Will comply
CANNOT	KANN NOTT	Unable to comply
REPEAT	REE- PEET	Repeat your instruction
AM LOST	AM LOSST	Position unknown
MAY DAY	MAYDAY	I am in distress
HIJACK ³⁾	HI-JACK	I have been hijacked
LAND (Place name)	LAAND (Place name)	I request to land at (place name)
DESCEND	DEE- SEND	I require descent

4 VISUAL SIGNALS FOR USE IN THE EVENT OF INTERCEPTION

4.1 Signals initiated by intercepting aircraft and responses by intercepted aircraft

Series	INTE	RCEPTING aircraft signals	Means	INTE	RCEPTED aircraft responds	Meaning
1.	flashing intervals of a heli above a the left or right if the copter) a slow lev to the right	NIGHT- Rocking aircraft and navigational lights at irregular s (and landing lights in the case copter) from a position slightly and ahead of, and normally to of intercepted aircraft (or to the he intercepted aircraft is a heliand after acknowledgement, a rel turn, normally to the left, (or ght in the case of a helicopter) desired heading.	You have been intercepted. Follow me			Understood, will comply.
	Note:	meteorological conditions or terrain may require the inter- cepting aircraft to reverse the positions and direction of turn given above in Series 1.				
	Note:	if the intercepted aircraft is not able to keep pace with the inter- cepting aircraft, the latter is expected to fly a series of race- track patterns and to rock the aircraft each time it passes the intercepted aircraft.				
2.	manoeu consistii grees oi	NIGHT- An abrupt break-away over from the intercepted aircraft and of a climbing turn of 90 derrore without crossing the line of the intercepted aircraft.	You may proceed.	DAY or	NIGHT - Rocking the aircraft.	Understood, will comply.
3.	DAY or NIGHT- Lowering landing gear (if fitted), showing steady landing lights and overflying runway in use of, if the intercepted aircraft is a helicopter, overflying the helicopter landing area. In the case of helicopters, the intercepting helicopter makes a landing approach, coming to hover near to the landing area.		Land at this aerodrome.	(if fitted) and follo and if, a or helice	NIGHT- Lowering landing gear,), showing steady landing lights owing the intercepting aircraft fter overflying the runway in use opter landing area, landing is red safe, proceeding to land.	Understood, will comply.

4.2 Signals initiated by intercepted aircraft and responses by intercepting aircraft

Series	INTERCEPTED aircraft signals	Meaning	INTERCEPTING aircraft responds	Meaning
4.	fitted) and flashing landing lights while passing over runway in use or helicopter landing area at a height exceeding 300 m (1000 ft) but not exceeding 600 m (2000 ft) (in the case of a helicopter, at a height exceeding 50 m (170 ft) but not	designated is inadequate.	DAY or NIGHT- If it is desired that the intercepted aicraft follow the intercepting aircraft to an alternate aerodrome, the intercepting aircraft raises its landing gear (if fitted) and uses the Series 1 signals prescribed for intercepting aircraft.	Understood, follow me.
	exceeding 100 m (330 ft)) above the aerodrome level, and continuing to circle runway in use or helicopter landing area. If unable to flash landing lights, flash any other lights available.		If it is decided to release the intercepted aircraft, the intercepting aircraft uses the Series 2 signals prescribed for intercepting aircraft.	
5.	DAY or NIGHT- Regular switching on and off of all aivalable lights but in such a manner as to be distinct from flashing lights.	Cannot comply.	DAY or NIGHT- Use series 2 signals prescribed for intercepting aircraft.	Understood.
6.	DAY or NIGHT- Irregular flashing of all available lights.	In distress.	DAY or NIGHT - Use series 2 signals prescribed for intercepting aircraft.	Understood.

Syllables to be emphasised are printed in bold.

The call sign required to be given is that used in radiotelephony communications with air traffic services units and corresponding to the aircraft identification in the flight plan.

Circumstances may not always permit, nor make desirable, the use of the phrase 'HIJACK'.