

AD ELEV -12

TWR	135.180	Lelystad Tower
	123.830	
	123.680	Lelystad Delivery
ATIS	120.730	Lelystad Information

ANNUAL RATE OF CHANGE 9' E

1. Helicopter exercise area (HELEX) AVBL northeast of FATO for helicopter exercises up to 50 FT.
2. FATO and HELEX only AVBL for local helicopter training operators.
3. FATO and HELEX only AVBL during UDP.

HOTSPOT
CAUTION:
DO NOT CROSS
THE HOLDING POSITION
MARKING WITHOUT
A CLEARANCE

HOTSPOT
CAUTION:
DO NOT CROSS
THE HOLDING POSITION
MARKING WITHOUT
A CLEARANCE

DIRECTIONS ARE MAGNETIC
ELEVATIONS IN FEET AMSL
DIMENSIONS IN METRES

A number line with two scales. The top scale is in metres, with markings at 0, 100, 200, 300, 400, and 500. The bottom scale is in feet, with markings at 0, 500, 1000, and 1500. A black bar is drawn above the metres scale, starting at 0 and ending at 500. A white bar is drawn below the feet scale, starting at 0 and ending at 1500. The black bar and the white bar are of the same length, illustrating that 500 metres is equal to 1500 feet.

RWY 05:
Do not cross red lights indicating displaced RWY end.
No lights beyond displaced RWY end.
Wind shear to be expected 140 + 25 KT.

RWY 23:
Do not cross red lights indicating displaced RWY end.
No lights beyond displaced RWY end.

	RWY HOLDING POSITION MARKING, PATTERN A
	MAX WHEEL SPAN 6 M
	ATC BDRY
	BLAST FENCE
	AIR TAXI ROUTE
	RWY END LIGHTS
	RWY GUARD LIGHTS

PHYSICAL CHARACTERISTICS				
RWY	DIRECTION	BEARING STRENGTH	SURFACE	THR COORDINATES
05	045°	PCN 55/F/B/W/T	ASPH	522648N 0053010E
23	225°	PCN 55/F/B/W/T	ASPH	522734N 0053132E

AIRAC AMDT 06/2026